


Pin	COMB
1	VSS
2	VSS
3	VDD
4	VDD
5	NC
6	/WR
7	/RD
8	/CS
9	RS
10	/RST
11	DB0
12	DB1
13	DB2
14	DB3
15	DB4
16	DB5
17	DB6
18	DB7
19	DB8
20	DB9
21	DB10
22	DB11
23	DB12
24	DB13
25	DB14
26	DB15
27	INT
28	Wst
29	NC
30	NC
31	NC
32	NC
33	NC
34	NC
35	NC
36	NC
37	SCL
38	SDI
39	SDD
40	SCS

Specification:

- 1). Driving:TFT, DotS:800*480, VDD:5V&3.3V
- 2). Viewing Direction:6 O'clock
- 3). Display mode:Normally White, Transmissive
- 4). Operating temp.: -20° C~+70° C
Storage temp.: -30° C~+80° C
- 5). Controller IC: RA8875
- 6). Backlight: White
- 7). Dimensions with mark "*" are important,
with mark "()" are referenced
- 8). All the raw materials are RoHS compliant

REV	REVISION RECORD	DATE	 深圳市三元晶科技有限公司 ShenZhen TCCLCD HI-Tech Co., Ltd.			
A	FIRST ISSUE	2015/11/06			GENERAL TOL: ±0.3 未注公差	
B			MODEL NO. 模组型号	SYC800480B070V8870	PAGE: 1 OF 1 页码	
C			APPROVED BY 审核	CHECKED BY 检查	DRAWING BY 绘图	UNIT: 单位mm
D			Liu 2015/11/06	Francis 2015/11/06	Luoxian 2015/11/06	PROJECTION 三角法